

Applicant : RICHARD BROWN Page 2
Serial Number : 10/690,807
Amendment in Response to Office Action of 10/22/2003

RECEIVED
CENTRAL FAX CENTER

OCT 11 2005

AMENDMENTS TO CLAIMS

What is claimed as being new and desired to be protected by
LETTERS PATENT of the United States is as follows:

1. (Original) A clam shell system for the formation of
complex work pieces in a fast and reliable manner comprising in
combination:

a work piece having an initial form with a long cylindrical
projection and a base;

an interior cylindrical component being composed of a
central inner beam, a central outer beam and coupled with a first
spring, the spring being adapted to apply pressure to the outer
beam to remove the work piece following manipulation and being
controlled by pressure applied to the inner beam;

an intermediate cylindrical component adapted to house the
interior cylindrical component and having four radially spaced
cylindrical control arms extending inwardly, an interior flange
and exterior pair of semi-conical molding arms having a coaxial
groove adjacent to a perpendicular recess within the molding arms
and being adapted to receive the work piece when extended and
forming the work piece when retracted;

an exterior housing having a cylindrical configuration with
an inner edge, an outer edge and a hollow interior being adapted

Applicant : RICHARD BROWN Page 3
Serial Number : 10/690,807
Amendment in Response to Office Action of 10/22/2003

to house the interior component and the intermediate component, the interior edge having a plurality of bores and a conical recess being adjacent to the exterior edge and terminating with a ledge, the conical recess being adapted to receive the molding arms of the intermediate cylindrical component;

a second spring adapted to rest upon the interior flange of the intermediate component and the ledge of the exterior housing forcing the molding arm to retract, when pressure is applied to the four control arms of the intermediate component the second spring is compressed and the molding arms are extended, pressure applied to the inner beam of the interior component while the molding arms are extended will cause the outer beam to remove the working piece; and

an interior end plate of a cylindrical configuration being adapted to be coupled to the bores on the inner edge of the exterior housing with a plurality of screws, the end plate having a central aperture to allow the passage of the inner beam of the interior component and four radially spaced apertures to allow the passage of the control arms of the intermediate component, the end plate allows the system to be controlled by exterior sources without affecting the internal parts.

Applicant : RICHARD BROWN Page 4
Serial Number : 10/690,807
Amendment in Response to Office Action of 10/22/2003

2. (Currently Amended) A clam shell system comprising:

a work piece;

~~an interior cylindrical component composed of a beam adapted to apply pressure to the beam to remove the work piece having an inner beam and an outer beam;~~

an intermediate cylindrical component having four radial spaced cylindrical control arms and an interior flange and an exterior pair of semi-conical molding arms adapted to receive a work piece; and

an exterior cylinder housing adapted to house the interior component and the intermediate component and having a ledge and a plurality of bores and a conical recess adapted to receive the molding arms of the intermediate cylindrical component; and

a first spring coupled to the outer beam and a second spring adapted to rest upon the interior flange of the intermediate component and the ledge of the exterior housing forcing the molding arm to retract; and

wherein when pressure is applied to the control arms of the intermediate component the second spring is compressed and the molding arms are extended, and wherein when pressure is applied to the inner beam of the interior component while the molding arms are extended the outer beam is caused to remove the working piece.

Applicant : RICHARD BROWN Page 5
Serial Number : 10/690,807
Amendment in Response to Office Action of 10/22/2003

3. (Canceled)

4. ~~The system asset forth in claim 2 and further including~~
A clam shell system comprising:

a work piece;

an interior cylindrical component having an inner beam and
an outer beam;

an intermediate cylindrical component having four radial
spaced cylindrical control arms and an interior flange and an
exterior pair of semi-conical molding arms adapted to receive a
work piece;

an exterior cylinder housing adapted to house the interior
component and the intermediate component and having an inner edge
and a plurality of bores and a conical recess adapted to receive
the molding arms of the intermediate cylindrical component; and

an interior end plate of a cylindrical configuration being
adapted to be coupled to the bores on the inner edge of the
exterior housing with a plurality of screws, the end plate having
a central aperture to allow the passage of the inner beam of the
interior component and four radial spaced apertures to allow the
passage of the control arms of the intermediate component, the
end plate allows adapted to allow the system to be controlled by
exterior sources without affecting the internal parts.